

Description

Length: 11/32", copper and cadmium plated

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS76A4011P
Minimum Qty (MOQ):	5
NSN:	3120-00-761-5314
ECCN:	EAR99
National Motor Freight:	114870, Bearing / Bushing Metal



P/N NAS76A4-011P Specifications

Overall Length:	0.3388 Inches Minimum And 0.3438 Inches Maximum
Body Outside Diameter:	0.3756 Inches Minimum And 0.3761 Inches Maximum
Body Inside Diameter:	0.2500 Inches Minimum And 0.2515 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Intermediate Layer
Material:	Copper Alloy 642 Overall
Material Document And Classification:	Qq-c-465 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas76 Professional/Industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A4-011P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.