

**Description**

Length: 11/32", copper and cadmium plated

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS76A4011P
Minimum Qty (MOQ):	5
NSN:	3120-00-761-5314
ECCN:	EAR99
National Motor Freight:	114870, Bearing / Bushing Metal



\* See page 2 for technical characteristics

## P/N NAS76A4-011P Specifications

<b>Overall Length:</b>	0.3388 Inches Minimum And 0.3438 Inches Maximum
<b>Body Outside Diameter:</b>	0.3756 Inches Minimum And 0.3761 Inches Maximum
<b>Body Inside Diameter:</b>	0.2500 Inches Minimum And 0.2515 Inches Maximum
<b>Corner Shape:</b>	Chamfered Inside Right Corner
<b>Corner Shape:</b>	Chamfered Inside Left Corner
<b>Corner Shape:</b>	Square Outside Left Corner
<b>Corner Shape:</b>	Square Outside Right Corner
<b>Surface Finish:</b>	125.0 Microinches Intermediate Layer
<b>Material:</b>	Copper Alloy 642 Overall
<b>Material Document And Classification:</b>	Qq-c-465 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	17c Solid, Plain, No Outside Flanges
<b>Style Designator:</b>	Solid, Plain, No Outside Flanges
<b>Specification/standard Data:</b>	80205-nas76 Professional/Industrial Association Standard

## How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A4-011P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.