

**Description**

NAS76A6-012 Sleeve Bushing

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS76A6012
Minimum Qty (MOQ):	5
NSN:	3120-00-661-7284
ECCN:	EAR99
National Motor Freight:	114870, Bearing / Bushing Metal

NO IMAGE  
AVAILABLE

## P/N NAS76A6-012 Specifications

<b>Overall Length:</b>	0.3700 Inches Minimum And 0.3750 Inches Maximum
<b>Body Outside Diameter:</b>	0.5006 Inches Minimum And 0.5013 Inches Maximum
<b>Body Inside Diameter:</b>	0.3750 Inches Minimum And 0.3765 Inches Maximum
<b>Corner Shape:</b>	Chamfered Inside Right Corner
<b>Corner Shape:</b>	Chamfered Inside Left Corner
<b>Corner Shape:</b>	Square Outside Left Corner
<b>Corner Shape:</b>	Square Outside Right Corner
<b>Surface Finish:</b>	125.0 Microinches Intermediate Layer
<b>Special Features:</b>	Id And Od To Be Parallel And Concentric Within 0.0030 Tir
<b>Material:</b>	Copper Alloy 630 Overall
<b>Material Document And Classification:</b>	Mil-b-6946 Mil Spec Single Material Response Overall
<b>Style Designator:</b>	17c Solid, Plain, No Outside Flanges
<b>Style Designator:</b>	Solid, Plain, No Outside Flanges
<b>Specification/standard Data:</b>	80205-nas76 Professional/industrial Association Standard

## How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A6-012> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.