

## **P/N NAS76A6-012**

### **Description**

NAS76A6-012 Sleeve Bushing

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS76A6012
Minimum Qty (MOQ):	5

NSN: 3120-00-661-7284

ECCN: EAR99

National Motor Freight: 114870, Bearing / Bushing Metal



<sup>\*</sup> See page 2 for technical characteristics

## P/N NAS76A6-012 Specifications

Overall Length:	0.3700 Inches Minimum And 0.3750 Inches Maximum
Body Outside Diameter:	0.5006 Inches Minimum And 0.5013 Inches Maximum
Body Inside Diameter:	0.3750 Inches Minimum And 0.3765 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Intermediate Layer
Special Features:	Id And Od To Be Parallel And Concentric Within 0.0030 Tir
Material:	Copper Alloy 630 Overall
Material Document And Classification:	Mil-b-6946 Mil Spec Single Material Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas76 Professional/industrial Association Standard

# **How to Order**

Order this sleeve bushing from our inventory online by visiting <a href="https://military-fasteners.com/bushings/NAS76A6-012">https://military-fasteners.com/bushings/NAS76A6-012</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/NAS76A6-012">https://military-fasteners.com/bushings/NAS76A6-012</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/NAS76A6-012">https://military-fasteners.com/bushings/NAS76A6-012</a> and selecting the quantity you