

Description

NAS76A6-012 Sleeve Bushing

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS76A6012
Minimum Qty (MOQ):	5
NSN:	3120-00-661-7284
ECCN:	EAR99
National Motor Freight:	114870, Bearing / Bushing Metal



* See page 2 for technical characteristics

P/N NAS76A6-012 Specifications

Overall Length:	0.3700 Inches Minimum And 0.3750 Inches Maximum
Body Outside Diameter:	0.5006 Inches Minimum And 0.5013 Inches Maximum
Body Inside Diameter:	0.3750 Inches Minimum And 0.3765 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Intermediate Layer
Special Features:	Id And Od To Be Parallel And Concentric Within 0.0030 Tir
Material:	Copper Alloy 630 Overall
Material Document And Classification:	Mil-b-6946 Mil Spec Single Material Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas76 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A6-012> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.