

Description

Length: 1-19/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS76A6119P
Minimum Qty (MOQ):	5 EA
NSN:	3120-00-196-5862
National Motor Freight:	114870, Bearing / Bushing Metal



NO IMAGE
AVAILABLE

P/N NAS76A6-119P Specifications

Overall Length:	1.5888 Inches Minimum And 1.5938 Inches Maximum
Body Outside Diameter:	0.5006 Inches Minimum And 0.5013 Inches Maximum
Body Inside Diameter:	0.3750 Inches Minimum And 0.3765 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Surface Finish:	125.0 Microinches Intermediate Layer
Material:	Copper Alloy 642 Overall
Material Document And Classification:	Qq-c-465 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas76 Professional/industrial Association Standard

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A6-119P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.