

Description

Length: 1-19/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------------------|
| SKU / Model: | NAS76A6119P |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 3120-00-196-5862 |
| National Motor Freight: | 114870, Bearing / Bushing Metal |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS76A6-119P Specifications

| | |
|---|---|
| Overall Length: | 1.5888 Inches Minimum And 1.5938 Inches Maximum |
| Body Outside Diameter: | 0.5006 Inches Minimum And 0.5013 Inches Maximum |
| Body Inside Diameter: | 0.3750 Inches Minimum And 0.3765 Inches Maximum |
| Corner Shape: | Chamfered Inside Right Corner |
| Corner Shape: | Chamfered Inside Left Corner |
| Corner Shape: | Square Outside Left Corner |
| Corner Shape: | Square Outside Right Corner |
| Surface Finish: | 125.0 Microinches Intermediate Layer |
| Material: | Copper Alloy 642 Overall |
| Material Document And Classification: | Qq-c-465 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Style Designator: | Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 80205-nas76 Professional/industrial Association Standard |

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76A6-119P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.