

Description

Length: 27/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS76B3027P
Minimum Qty (MOQ):	5
NSN:	3120-01-243-0802
ECCN:	EAR99
National Motor Freight:	114870, Bearing / Bushing Metal



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS76B3-027P Specifications

Overall Length:	0.8388 Inches Minimum And 0.8438 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Special Features:	Color Olive Drab
Material:	Copper Alloy 172 Overall Or Copper Alloy 173 Overall
Material Document And Classification:	Qq-c-530 Fed Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas76 Professional/Industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS76B3-027P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.