

## P/N NAS77-5-025

## **Description**

Length: 1/4", NAS77 series bushing

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS775025


Minimum Qty (MOQ):

NSN: 3120-00-661-4377

ECCN: EAR99

National Motor Freight: 115620, Bushings Noi I / S







<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS77-5-025 Specifications**

Overall Length:	0.3020 Inches Minimum And 0.3170 Inches Maximum
Body Outside Diameter:	0.4381 Inches Minimum And 0.4386 Inches Maximum
Body Inside Diameter:	0.3125 Inches Minimum And 0.3140 Inches Maximum
Flange Outside Diameter:	0.5520 Inches Minimum And 0.5720 Inches Maximum
Flange Width:	0.0570 Inches Minimum And 0.0620 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Left Flange Outside Right Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Corner Shape:	Undercut Left Flange Body Corner
Surface Finish:	100.0 Microinches Intermediate Layer
Material:	Steel Comp 8630 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	22c Solid, External Flange One End
Style Designator:	Solid, External Flange One End
Specification/standard Data:	80205-nas77 Professional/industrial Association Standard

### **How to Order**

Order this sleeve bushing from our inventory online by visiting <a href="https://military-fasteners.com/bushings/sleeve+bushings/NAS77-5-025">https://military-fasteners.com/bushings/sleeve+bushings/NAS77-5-025</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.