

Description

NAS77-5-043 Sleeve Bushing

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS775043 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 3120-01-547-7402 |
| ECCN: | EAR99 |



NO IMAGE
AVAILABLE

P/N NAS77-5-043 Specifications

| | |
|---|--|
| Overall Length: | 0.4330 Inches Minimum And 0.4970 Inches Maximum |
| Body Outside Diameter: | 0.4381 Inches Minimum And 0.4386 Inches Maximum |
| Body Inside Diameter: | 0.3125 Inches Minimum And 0.3140 Inches Maximum |
| Flange Outside Diameter: | 0.5520 Inches Minimum And 0.5720 Inches Maximum |
| End Item Identification: | T-6 Aircraft |
| Flange Width: | 0.0570 Inches Minimum And 0.0620 Inches Maximum |
| Corner Shape: | Chamfered Inside Right Corner |
| Corner Shape: | Chamfered Inside Left Corner |
| Corner Shape: | Square Left Flange Outside Right Corner |
| Corner Shape: | Square Outside Left Corner |
| Corner Shape: | Square Outside Right Corner |
| Corner Shape: | Undercut Left Flange Body Corner |
| Surface Finish: | 100.0 Microinches Intermediate Layer |
| Material: | Steel Comp 4130 Overall Or Steel Comp 8630 Overall |
| Material Document And Classification: | Mil-s-6798 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Ty2, Cl 3 Fed Spec Single Treatment Response Overall |
| Style Designator: | 22c Solid, External Flange One End |
| Specification/standard Data: | 80205-nas77 Professional/industrial Association Standard |

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77-5-043> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.