

Description

NAS77-6-024 Sleeve Bushing

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS776024
Minimum Qty (MOQ):	10
NSN:	3120-00-517-8336
ECCN:	EAR99
National Motor Freight:	115620, Bushings Noi I / S

NO IMAGE
AVAILABLE

P/N NAS77-6-024 Specifications

Overall Length:	0.2920 Inches Minimum And 0.3070 Inches Maximum
Body Outside Diameter:	0.5006 Inches Minimum And 0.5013 Inches Maximum
Body Inside Diameter:	0.3750 Inches Minimum And 0.3765 Inches Maximum
Flange Outside Diameter:	0.6150 Inches Minimum And 0.6350 Inches Maximum
Flange Width:	0.0570 Inches Minimum And 0.0620 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Left Flange Outside Right Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Corner Shape:	Undercut Left Flange Body Corner
Surface Finish:	100.0 Microinches Intermediate Layer
Material:	Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	22c Solid, External Flange One End
Style Designator:	Solid, External Flange One End
Specification/standard Data:	80205-nas77 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77-6-024> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.