

**Description**

NAS77-6-025P Sleeve Bushing

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS776025P
Minimum Qty (MOQ):	5
NSN:	3120-01-334-7986
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS77-6-025P Specifications

<b>Overall Length:</b>	0.3020 Inches Minimum And 0.3170 Inches Maximum
<b>Body Outside Diameter:</b>	0.5006 Inches Minimum And 0.5013 Inches Maximum
<b>Body Inside Diameter:</b>	0.3750 Inches Minimum And 0.3765 Inches Maximum
<b>Flange Outside Diameter:</b>	0.6150 Inches Minimum And 0.6350 Inches Maximum
<b>Flange Width:</b>	0.0570 Inches Minimum And 0.0620 Inches Maximum
<b>Corner Shape:</b>	Chamfered Inside Right Corner
<b>Corner Shape:</b>	Chamfered Inside Left Corner
<b>Corner Shape:</b>	Square Left Flange Outside Right Corner
<b>Corner Shape:</b>	Square Outside Left Corner
<b>Corner Shape:</b>	Square Outside Right Corner
<b>Corner Shape:</b>	Undercut Left Flange Body Corner
<b>Surface Finish:</b>	100.0 Microinches Overall
<b>Special Features:</b>	Outside Diameter Corners Have A Chamfer That Measures 0.0050 In. Min.,0.0150 In. Max.,45 Degree Angle; Itemhas A Press Fit
<b>Material:</b>	Steel Comp 4130 Overall Or Steel Comp 8630 Overall
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec Single Material Response Overall Or Mil-s-6050 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type Ii,class 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	22c Solid, External Flange One End
<b>Specification/standard Data:</b>	80205-nas77 Professional/industrial Association Standard

## How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77-6-025P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.