

**Description**

Length: 13/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS777035   |
| Minimum Qty (MOQ):      | 10 EA   |
| NSN:                    | 3120-01-326-4361                                    |
| National Motor Freight: | 114850, Bearing / Bushing O / T Ball / Roller I / S |



\* See page 2 for technical characteristics

## P/N NAS77-7-035 Specifications

|   |  |
|---|--|
| <b>Overall Length:</b>                                | 0.4120 Inches Nominal  |
| <b>Body Outside Diameter:</b>                         | 0.5631 Inches Minimum And 0.5638 Inches Maximum  |
| <b>Body Inside Diameter:</b>                          | 0.4375 Inches Minimum And 0.4390 Inches Maximum  |
| <b>Flange Outside Diameter:</b>                       | 0.6770 Inches Minimum And 0.6970 Inches Maximum  |
| <b>Flange Width:</b>                                  | 0.0570 Inches Minimum And 0.0620 Inches Maximum  |
| <b>Corner Shape:</b>                                  | Chamfered Inside Right Corner  |
| <b>Corner Shape:</b>                                  | Chamfered Inside Left Corner   |
| <b>Corner Shape:</b>                                  | Square Left Flange Outside Right Corner  |
| <b>Corner Shape:</b>                                  | Square Outside Left Corner   |
| <b>Corner Shape:</b>                                  | Square Outside Right Corner  |
| <b>Corner Shape:</b>                                  | Undercut Left Flange Body Corner   |
| <b>Material:</b>                                      | Steel Comp 4130 Overall Or Steel Comp 8630 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall  |
| <b>Style Designator:</b>                              | 22c Solid, External Flange One End   |
| <b>Specification/standard Data:</b>                   | 81205-nas77 Professional/Industrial Association Standard   |

## How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77-7-035> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.