

Description

Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS777035
Minimum Qty (MOQ):	10 EA
NSN:	3120-01-326-4361
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS77-7-035 Specifications

Overall Length:	0.4120 Inches Nominal
Body Outside Diameter:	0.5631 Inches Minimum And 0.5638 Inches Maximum
Body Inside Diameter:	0.4375 Inches Minimum And 0.4390 Inches Maximum
Flange Outside Diameter:	0.6770 Inches Minimum And 0.6970 Inches Maximum
Flange Width:	0.0570 Inches Minimum And 0.0620 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Left Flange Outside Right Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Corner Shape:	Undercut Left Flange Body Corner
Material:	Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	22c Solid, External Flange One End
Specification/standard Data:	81205-nas77 Professional/Industrial Association Standard

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77-7-035> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.