

**Description**

Length: 39/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS777055
Minimum Qty (MOQ):	10 EA
NSN:	3120-00-661-4256
National Motor Freight:	114850, Bearing / Bushing O / T Ball / Roller I / S

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS77-7-055 Specifications

<b>Overall Length:</b>	0.6020 Inches Minimum And 0.6170 Inches Maximum
<b>Body Outside Diameter:</b>	0.5631 Inches Minimum And 0.5638 Inches Maximum
<b>Body Inside Diameter:</b>	0.4375 Inches Minimum And 0.4390 Inches Maximum
<b>Flange Outside Diameter:</b>	0.6770 Inches Minimum And 0.6970 Inches Maximum
<b>Flange Width:</b>	0.0570 Inches Minimum And 0.0620 Inches Maximum
<b>Corner Shape:</b>	Chamfered Inside Right Corner
<b>Corner Shape:</b>	Chamfered Inside Left Corner
<b>Corner Shape:</b>	Square Left Flange Outside Right Corner
<b>Corner Shape:</b>	Square Outside Left Corner
<b>Corner Shape:</b>	Square Outside Right Corner
<b>Corner Shape:</b>	Undercut Left Flange Body Corner
<b>Surface Finish:</b>	100.0 Microinches Intermediate Layer
<b>Material:</b>	Steel Comp 8630 Overall Or Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	22c Solid, External Flange One End
<b>Style Designator:</b>	Solid, External Flange One End
<b>Specification/standard Data:</b>	80205-nas77 Professional/industrial Association Standard

## How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77-7-055> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.