

**Description**


NAS77-8-012 Sleeve Bushing

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS778012   |
| Minimum Qty (MOQ):      | 2   |
| NSN:                    | 3120-00-662-8349                                    |
| ECCN:                   | EAR99   |
| National Motor Freight: | 114850, Bearing / Bushing O / T Ball / Roller I / S |



## P/N NAS77-8-012 Specifications

|   |  |
|---|--|
| <b>Overall Length:</b>                                | 0.1720 Inches Minimum And 0.1870 Inches Maximum  |
| <b>Body Outside Diameter:</b>                         | 0.6257 Inches Minimum And 0.6265 Inches Maximum  |
| <b>Body Inside Diameter:</b>                          | 0.5000 Inches Minimum And 0.5015 Inches Maximum  |
| <b>Flange Outside Diameter:</b>                       | 0.7400 Inches Minimum And 0.7600 Inches Maximum  |
| <b>Flange Width:</b>                                  | 0.0570 Inches Minimum And 0.0620 Inches Maximum  |
| <b>Corner Shape:</b>                                  | Chamfered Inside Right Corner  |
| <b>Corner Shape:</b>                                  | Chamfered Inside Left Corner   |
| <b>Corner Shape:</b>                                  | Square Left Flange Outside Right Corner  |
| <b>Corner Shape:</b>                                  | Square Outside Left Corner   |
| <b>Corner Shape:</b>                                  | Square Outside Right Corner  |
| <b>Corner Shape:</b>                                  | Undercut Left Flange Body Corner   |
| <b>Surface Finish:</b>                                | 100.0 Microinches Intermediate Layer   |
| <b>Material:</b>                                      | Steel Comp 8630 Overall Or Steel Comp 4130 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall  |
| <b>Style Designator:</b>                              | 22c Solid, External Flange One End   |
| <b>Style Designator:</b>                              | Solid, External Flange One End   |
| <b>Specification/standard Data:</b>                   | 80205-nas77 Professional/industrial Association Standard   |

## How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77-8-012> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.