



Military-Fasteners.com

P/N NAS7700-6

Description

Fastener Length: 5/8", Thread: 4-40, Thread Length: 15/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS77006
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-559-7835
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel



* See page 2 for technical characteristics

P/N NAS7700-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.238 Inches Nominal
Fastener Length:	0.598 Inches Minimum And 0.628 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Grip Diameter:	0.111 Inches Minimum And 0.112 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	C-130 Amp Cmb
Nominal Thread Diameter:	0.112 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:	40
Material:	Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7700-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.