

Description

Fastener Length: 5/8", Thread: 4-40, Thread Length: 15/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS77006 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-559-7835 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



* See page 2 for technical characteristics

P/N NAS7700-6 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.238 Inches Nominal |
| Fastener Length: | 0.598 Inches Minimum And 0.628 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.205 Inches Minimum And 0.219 Inches Maximum |
| Head Height: | 0.070 Inches Minimum And 0.080 Inches Maximum |
| Grip Diameter: | 0.111 Inches Minimum And 0.112 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| End Item Identification: | C-130 Amp Cmb |
| Nominal Thread Diameter: | 0.112 Inches |
| Grip Length: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Thread Quantity Per Inch: | 40 |
| Material: | Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7700-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.