

P/N NAS7701-4

Description

Fastener Length: 17/32", Thread: 6-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS77014
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-369-3506
Schedule B:	7318.15.8085
ECCN:	EAR99

093486, Bolts, nuts Or Screws, Noi (sub 3)



National Motor Freight:

^{*} See page 2 for technical characteristics

P/N NAS7701-4 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Nominal
Fastener Length:	0.511 Inches Minimum And 0.541 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Grip Diameter:	0.1365 Inches Minimum And 0.1375 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas7701 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS7701-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.