

P/N NAS7702-1

Description

length: 0.385", grip: 0.062", thread: 8-32, pan head close tolerance bolt, cadmium plated alloy steel, philips recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS77021

Minimum Qty (MOQ): 100

NSN: 5305-01-366-4534

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS7702-1 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.370 Inches Minimum And 0.400 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Grip Diameter:	0.1625 Inches Minimum And 0.1655 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.052 Inches Minimum And 0.072 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Chromate Overall And Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas7702 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS7702-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.