

Description

Fastener Length: 1-57/64", Thread: 10-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS770325
Minimum Qty (MOQ):	1
NSN:	5305-01-532-9956
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS7703-25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	1.870 Inches Minimum And 1.900 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	C130 Amp Cmb
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.552 Inches Minimum And 1.572 Inches Maximum
Thread Quantity Per Inch:	32
Part Name Assigned By Controlling Agency:	Bolt,pan Head,close Tolerance,short Thread
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp E4340 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Ams6415 Assn Std 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7703-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.