



Military-Fasteners.com

P/N NAS7703-25

Description

Fastener Length: 1-57/64", Thread: 10-32, Thread Length: 5/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS770325
Minimum Qty (MOQ):	1
NSN:	5305-01-532-9956
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



\* See page 2 for technical characteristics

## P/N NAS7703-25 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	1.870 Inches Minimum And 1.900 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.357 Inches Minimum And 0.373 Inches Maximum
<b>Head Height:</b>	0.122 Inches Minimum And 0.133 Inches Maximum
<b>Grip Diameter:</b>	0.188 Inches Minimum And 0.189 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	C130 Amp Cmb
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	1.552 Inches Minimum And 1.572 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Part Name Assigned By Controlling Agency:</b>	Bolt,pan Head,close Tolerance,short Thread
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp E4340 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Ams6415 Assn Std 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7703-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.