

Description

Fastener Length: 2-29/64", Thread: 10-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS770334
Minimum Qty (MOQ):	10
NSN:	5305-01-611-5761
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS7703-34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	2.433 Inches Minimum And 2.463 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Grip Diameter:	0.182 Inches Minimum And 0.183 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	C130 Amp Cmb
Nominal Thread Diameter:	0.190 Inches
Grip Length:	2.115 Inches Minimum And 2.135 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Steel Comp 4140 Overall
Surface Treatment:	Chromium Grip
Surface Treatment:	Cadmium Head
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7703-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.