

Description

Fastener Length: 2-29/64", Thread: 10-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS770334 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-611-5761 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N NAS7703-34 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.323 Inches Nominal |
| Fastener Length: | 2.433 Inches Minimum And 2.463 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.357 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Grip Diameter: | 0.182 Inches Minimum And 0.183 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| End Item Identification: | C130 Amp Cmb |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 2.115 Inches Minimum And 2.135 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Material: | Steel Comp 4140 Overall |
| Surface Treatment: | Chromium Grip |
| Surface Treatment: | Cadmium Head |
| Thread Series Designator: | Unjf |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7703-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.