

Description

Fastener Length: 21/64", Thread: 10-32, Thread Length: 21/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS770362 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5305-01-468-4248 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS7703-62 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.323 Inches Nominal |
| Fastener Length: | 0.323 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.188 Inches Minimum And 0.189 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Grip Diameter: | 0.211 Inches Minimum And 0.212 Inches Maximum |
| Internal Drive Style: | Cross Recess Type Iii |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 3.875 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Thread Pitch In Millimeters: | 0.7 |
| External Thread Tolerance Class: | 3a |
| Material: | Steel Comp 4140 Overall Or Steel Comp 4340 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Overall Or Ams6415 Assn Std 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,typeii,class2 Fed Spec 1st Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7703-62> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.