

# **P/N NAS7703L2**

## **Description**

Fastener Length: 7/16", Thread: 10-32, Thread Length: 5/16

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

### NAS7703-L2

SKU / Model:	NAS7703L2
Minimum Qty (MOQ):	1
NSN:	5305-01-392-1080
Schedule B:	7318.15.8085
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS7703L2 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.448 Inches Nominal
Head Style:	Pan
Head Diameter:	0.670 Inches Nominal
Head Height:	0.127 Inches Nominal
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type Ii
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

## **How to Order**

Order this close tolerance screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS7703L2">https://military-fasteners.com/screws/close+tolerance+screws/NAS7703L2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS7703L2">https://military-fasteners.com/screws/close+tolerance+screws/NAS7703L2</a> and selecting the