

Description

Length: 5/32", NAS77 series bushing

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------------------|
| SKU / Model: | NAS77A3010P |
| Minimum Qty (MOQ): | 10 |
| NSN: | 3120-00-554-4842 |
| ECCN: | EAR99 |
| National Motor Freight: | 114870, Bearing / Bushing Metal |



* See page 2 for technical characteristics

P/N NAS77A3-010P Specifications

| | |
|---|---|
| Overall Length: | 0.1520 Inches Minimum And 0.1670 Inches Maximum |
| Body Outside Diameter: | 0.3131 Inches Minimum And 0.3136 Inches Maximum |
| Body Inside Diameter: | 0.1900 Inches Minimum And 0.1915 Inches Maximum |
| Flange Outside Diameter: | 0.4270 Inches Minimum And 0.4470 Inches Maximum |
| Flange Width: | 0.0570 Inches Minimum And 0.0620 Inches Maximum |
| Corner Shape: | Chamfered Inside Right Corner |
| Corner Shape: | Chamfered Inside Left Corner |
| Corner Shape: | Square Left Flange Outside Right Corner |
| Corner Shape: | Square Outside Left Corner |
| Corner Shape: | Square Outside Right Corner |
| Corner Shape: | Undercut Left Flange Body Corner |
| Surface Finish: | 100.0 Microinches Intermediate Layer |
| Material: | Copper Alloy 642 Overall |
| Material Document And Classification: | Qq-c-465 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | 22c Solid, External Flange One End |
| Style Designator: | Solid, External Flange One End |
| Specification/standard Data: | 80205-nas77 Professional/Industrial Association Standard |

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77A3-010P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.