



★ FASTENERS

Military-Fasteners.com

P/N NAS77A3-015

Description

Length: 9/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS77A3015
Minimum Qty (MOQ):	10
NSN:	3120-01-497-3426
ECCN:	EAR99
National Motor Freight:	114820, Bearings / Bushings Noi Ball / Roller



* See page 2 for technical characteristics

P/N NAS77A3-015 Specifications

Overall Length:	0.1450 Inches Minimum And 0.1550 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Flange Outside Diameter:	0.4270 Inches Minimum And 0.4470 Inches Maximum
End Item Identification:	M3p Reu-I
Flange Width:	0.0620 Inches Minimum And 0.0670 Inches Maximum
Corner Shape:	Chamfered All Corners
Material:	Copper Alloy 642 Overall Or Copper Alloy 630 Overall
Material Document And Classification:	Qq-c-465 Fed Spec 1st Material Response Overall Or Ams4640 Assn Std 2nd Material Response Overall
Style Designator:	22c Solid, External Flange One End

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77A3-015> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.