

**Description**

Length: 17/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS77A3020
Minimum Qty (MOQ):	5 EA
NSN:	3120-00-945-4564
National Motor Freight:	114870, Bearing / Bushing Metal

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS77A3-020 Specifications

<b>Overall Length:</b>	0.2520 Inches Minimum And 0.2670 Inches Maximum
<b>Body Outside Diameter:</b>	0.3131 Inches Minimum And 0.3136 Inches Maximum
<b>Body Inside Diameter:</b>	0.1900 Inches Minimum And 0.1915 Inches Maximum
<b>Flange Outside Diameter:</b>	0.4270 Inches Minimum And 0.4470 Inches Maximum
<b>Flange Width:</b>	0.0570 Inches Minimum And 0.0620 Inches Maximum
<b>Corner Shape:</b>	Chamfered Inside Right Corner
<b>Corner Shape:</b>	Chamfered Inside Left Corner
<b>Corner Shape:</b>	Square Left Flange Outside Right Corner
<b>Corner Shape:</b>	Square Outside Left Corner
<b>Corner Shape:</b>	Square Outside Right Corner
<b>Corner Shape:</b>	Undercut Left Flange Body Corner
<b>Surface Finish:</b>	100.0 Microinches Intermediate Layer
<b>Special Features:</b>	Id And Od To Be Parallel And Concentric Within 0.0030 Tir
<b>Material:</b>	Copper Alloy 642 Overall
<b>Material Document And Classification:</b>	Qq-c-465 Fed Spec Single Material Response Overall
<b>Style Designator:</b>	22c Solid, External Flange One End
<b>Specification/standard Data:</b>	80205-nas77 Professional/Industrial Association Standard

## How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77A3-020> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.