

**Description**

Length: 19/64", NAS77 series bushing

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS77A3024P
Minimum Qty (MOQ):	10
NSN:	3120-01-129-9152
National Motor Freight:	114870, Bearing / Bushing Metal

NO IMAGE  
AVAILABLE

## P/N NAS77A3-024P Specifications

<b>Overall Length:</b>	0.2920 Inches Minimum And 0.3070 Inches Maximum
<b>Body Outside Diameter:</b>	0.3131 Inches Minimum And 0.3136 Inches Maximum
<b>Body Inside Diameter:</b>	0.1900 Inches Minimum And 0.1915 Inches Maximum
<b>Flange Outside Diameter:</b>	0.4270 Inches Minimum And 0.4470 Inches Maximum
<b>Flange Width:</b>	0.0570 Inches Minimum And 0.0620 Inches Maximum
<b>Corner Shape:</b>	Chamfered Inside Right Corner
<b>Corner Shape:</b>	Chamfered Inside Left Corner
<b>Corner Shape:</b>	Square Left Flange Outside Right Corner
<b>Corner Shape:</b>	Square Outside Left Corner
<b>Corner Shape:</b>	Square Outside Right Corner
<b>Corner Shape:</b>	Undercut Left Flange Body Corner
<b>Surface Finish:</b>	100.0 Microinches Overall
<b>Material:</b>	Copper Alloy 642 Overall Or Copper Alloy 630 Overall
<b>Material Document And Classification:</b>	Qq-c-465 Fed Spec 1st Material Response Overall Or Qq-b-679 Fed Spec 2nd Material Response Overall Or Ams 4640 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	22c Solid, External Flange One End
<b>Specification/standard Data:</b>	80205-nas77 Professional/industrial Association Standard

## How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77A3-024P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.