

P/N NAS77A3-031

Description

Length: 3/8",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS77A3031

Minimum Qty (MOQ): 10

NSN: 3120-00-849-7606

ECCN: EAR99

National Motor Freight: 115620, Bushings Noi I / S









P/N NAS77A3-031 Specifications

Overall Length:	0.3620 Inches Minimum And 0.3770 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Flange Outside Diameter:	0.4270 Inches Minimum And 0.4470 Inches Maximum
Flange Width:	0.0570 Inches Minimum And 0.0620 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Left Flange Outside Right Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Corner Shape:	Undercut Left Flange Body Corner
Surface Finish:	100.0 Microinches Intermediate Layer
Special Features:	Id And Od To Be Parallel And Concentric Within 0.0030 Tir
Material:	Copper Alloy 642 Overall
Material Document And Classification:	Qq-c-465 Fed Spec Single Material Response Overall
Style Designator:	22c Solid, External Flange One End
Specification/standard Data:	80205-nas77 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting https://military-fasteners.com/bushings/sleeve+bushings/NAS77A3-031 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bushings/NAS77A3-031 and selecting the quantity you