

Description

Length: 25/32",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS77A3073
Minimum Qty (MOQ):	5
NSN:	3120-01-309-4841
ECCN:	EAR99
National Motor Freight:	114870, Bearing / Bushing Metal



P/N NAS77A3-073 Specifications

Overall Length:	0.7920 Inches Nominal
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Flange Outside Diameter:	0.4270 Inches Minimum And 0.4470 Inches Maximum
Flange Width:	0.0570 Inches Minimum And 0.0620 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Left Flange Outside Right Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Corner Shape:	Undercut Left Flange Body Corner
Surface Finish:	100.0 Microinches Overall
Special Features:	Id And Od To Be Concentric Within 0.003 Tir
Material:	Copper Alloy 642 Overall Or Copper Alloy 630 Overall
Material Document And Classification:	Astm B124 Assn Std All Material Responses Overall Or Astm B150 Assn Std All Material Responses Overall Or Astm B283 Assn Std 1st Material Response Overall Or Ams 4640 Assn Std 2nd Material Response Overall
Style Designator:	22c Solid, External Flange One End
Specification/standard Data:	80205-nas77 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77A3-073> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.