

Description

Length: 57/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS77A3083
Minimum Qty (MOQ):	5 EA
NSN:	3120-01-119-5112
National Motor Freight:	114870, Bearing / Bushing Metal

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS77A3-083 Specifications

Overall Length:	0.8820 Inches Minimum And 0.8970 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Flange Outside Diameter:	0.4270 Inches Minimum And 0.4470 Inches Maximum
Flange Width:	0.0570 Inches Minimum And 0.0620 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Left Flange Outside Right Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Corner Shape:	Undercut Left Flange Body Corner
Surface Finish:	100.0 Microinches Intermediate Layer
Material:	Copper Alloy 642 Overall
Material Document And Classification:	Qq-c-465 Fed Spec Single Material Response Overall
Style Designator:	22c Solid, External Flange One End
Specification/standard Data:	80205-nas77 Professional/industrial Association Standard

How to Order

Order this bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77A3-083> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.