

P/N NAS77A3-087

Military-Fasteners.com

Description

Length: 15/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS77A3087
Minimum Qty (MOQ):	1
NSN:	3120-01-128-9038
ECCN:	EAR99
National Motor Freight:	114870, Bearing / Bushing Metal



P/N NAS77A3-087 Specifications

Overall Length:	0.9220 Inches Minimum And 0.9370 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Flange Outside Diameter:	0.4270 Inches Minimum And 0.4470 Inches Maximum
Flange Width:	0.0570 Inches Minimum And 0.0620 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Left Flange Outside Right Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Corner Shape:	Undercut Left Flange Body Corner
Surface Finish:	100.0 Microinches Intermediate Layer
Material:	Copper Alloy Overall
Style Designator:	22c Solid, External Flange One End
Specification/standard Data:	80205-nas77 Government Standard

How to Order

Order this sleeve bushing from our inventory online by visiting <u>https://military-fasteners.com/bushings/sleeve+bushings/NAS77A3-087</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.