

P/N NAS77A3-088

Description

Length: 15/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS77A3088

Minimum Qty (MOQ):

NSN: 3120-01-140-7842

ECCN: EAR99

National Motor Freight: 114870, Bearing / Bushing Metal



^{*} See page 2 for technical characteristics

P/N NAS77A3-088 Specifications

Overall Length:	0.9320 Inches Minimum And 0.9470 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Flange Outside Diameter:	0.4270 Inches Minimum And 0.4470 Inches Maximum
Flange Width:	0.0570 Inches Minimum And 0.0620 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Left Flange Outside Right Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Corner Shape:	Undercut Left Flange Body Corner
Surface Finish:	100.0 Microinches Overall
Material:	Copper Alloy 642 Overall Or Copper Alloy 630 Overall
Material Document And	Qq-c-465 Fed Spec 1st Material Response Overall Or Qq-b-679 Fed Spec 2nd Material Response Overall Or Ams 4640 Assn Std 2nd
Classification:	Material Response Overall
Style Designator:	22c Solid, External Flange One End
Specification/standard Data:	80205-nas77 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting https://military-fasteners.com/bushings/sleeve+bushings/NAS77A3-088 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.