

**Description**

Length: 61/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS77A3090
Minimum Qty (MOQ):	5
NSN:	3120-01-310-1633
ECCN:	EAR99
National Motor Freight:	114870, Bearing / Bushing Metal



\* See page 2 for technical characteristics

## P/N NAS77A3-090 Specifications

<b>Overall Length:</b>	0.9520 Inches Minimum And 0.9670 Inches Maximum
<b>Body Outside Diameter:</b>	0.3131 Inches Minimum And 0.3136 Inches Maximum
<b>Body Inside Diameter:</b>	0.1900 Inches Minimum And 0.1915 Inches Maximum
<b>Flange Outside Diameter:</b>	0.4270 Inches Minimum And 0.4470 Inches Maximum
<b>Flange Width:</b>	0.0570 Inches Minimum And 0.0620 Inches Maximum
<b>Corner Shape:</b>	Chamfered Inside Right Corner
<b>Corner Shape:</b>	Chamfered Inside Left Corner
<b>Corner Shape:</b>	Square Left Flange Outside Right Corner
<b>Corner Shape:</b>	Square Outside Left Corner
<b>Corner Shape:</b>	Square Outside Right Corner
<b>Corner Shape:</b>	Undercut Left Flange Body Corner
<b>Surface Finish:</b>	100.0 Microinches Overall
<b>Material:</b>	Copper Alloy 642 Overall Or Copper Alloy 630 Overall
<b>Material Document And Classification:</b>	Qq-c-00465 Fed Spec 1st Material Response Overall Or Ams 4640 Assn Std 2nd Material Response Overall
<b>Style Designator:</b>	22c Solid, External Flange One End
<b>Specification/standard Data:</b>	80205-nas77 Professional/industrial Association Standard

## How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77A3-090> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.