

## P/N NAS77A3-099

### **Description**

Length: 1-3/64

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS77A3099
Minimum Qty (MOQ): 5

NSN: 3120-01-115-0793

ECCN: EAR99

National Motor Freight: 114870, Bearing / Bushing Metal



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS77A3-099 Specifications

Overall Length:	1.0420 Inches Minimum And 1.0570 Inches Maximum
Body Outside Diameter:	0.3131 Inches Minimum And 0.3136 Inches Maximum
Body Inside Diameter:	0.1900 Inches Minimum And 0.1915 Inches Maximum
Flange Outside Diameter:	0.4270 Inches Minimum And 0.4470 Inches Maximum
Flange Width:	0.0570 Inches Minimum And 0.0620 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Left Flange Outside Right Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Corner Shape:	Undercut Left Flange Body Corner
Surface Finish:	100.0 Microinches Intermediate Layer
Material:	Copper Alloy 642 Overall
Material Document And Classification:	Qq-c-465 Fed Spec Single Material Response Overall
Style Designator:	22c Solid, External Flange One End
Specification/standard Data:	80205-nas77 Professional/industrial Association Standard

## **How to Order**

Order this sleeve bushing from our inventory online by visiting <a href="https://military-fasteners.com/bushings/sleeve+bushings/NAS77A3-099">https://military-fasteners.com/bushings/sleeve+bushings/NAS77A3-099</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.