

**Description**

NAS77A4-014P Sleeve Bushing

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS77A4014P   |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 3120-01-047-1100                                    |
| ECCN:                   | EAR99   |
| National Motor Freight: | 114850, Bearing / Bushing O / T Ball / Roller I / S |



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS77A4-014P Specifications

|   |   |
|---|---|
| <b>Overall Length:</b>                                | 0.1920 Inches Minimum And 0.2070 Inches Maximum               |
| <b>Body Outside Diameter:</b>                         | 0.3756 Inches Minimum And 0.3761 Inches Maximum               |
| <b>Body Inside Diameter:</b>                          | 0.2500 Inches Minimum And 0.2515 Inches Maximum               |
| <b>Flange Outside Diameter:</b>                       | 0.4900 Inches Minimum And 0.5100 Inches Maximum               |
| <b>Flange Width:</b>                                  | 0.0570 Inches Minimum And 0.0620 Inches Maximum               |
| <b>Corner Shape:</b>                                  | Chamfered Inside Right Corner                                 |
| <b>Corner Shape:</b>                                  | Chamfered Inside Left Corner                                  |
| <b>Corner Shape:</b>                                  | Square Left Flange Outside Right Corner                       |
| <b>Corner Shape:</b>                                  | Square Outside Left Corner                                    |
| <b>Corner Shape:</b>                                  | Square Outside Right Corner                                   |
| <b>Corner Shape:</b>                                  | Undercut Left Flange Body Corner                              |
| <b>Surface Finish:</b>                                | 100.0 Microinches Intermediate Layer                          |
| <b>Material:</b>                                      | Copper Alloy 642 Overall                                      |
| <b>Material Document And Classification:</b>          | Qq-c-465 Fed Spec Single Material Response Overall            |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| <b>Style Designator:</b>                              | 22c Solid, External Flange One End                            |
| <b>Specification/standard Data:</b>                   | 80205-nas77 Professional/Industrial Association Standard      |

## How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77A4-014P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.