

Description

NAS77A5-028 Sleeve Bushing

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------|
| SKU / Model: | NAS77A5028 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 3120-01-478-5701 |
| ECCN: | EAR99 |
| National Motor Freight: | 114800, Bearing,roller,thrust |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS77A5-028 Specifications

| | |
|--|--|
| Overall Length: | 0.3320 Inches Minimum And 0.3470 Inches Maximum |
| Body Outside Diameter: | 0.4381 Inches Minimum And 0.4386 Inches Maximum |
| Body Inside Diameter: | 0.3125 Inches Minimum And 0.3140 Inches Maximum |
| Flange Outside Diameter: | 0.5520 Inches Minimum And 0.5720 Inches Maximum |
| Flange Width: | 0.0570 Inches Minimum And 0.0620 Inches Maximum |
| Corner Shape: | Square All Corners |
| Part Name Assigned By Controlling Agency: | Bushing, Flanged |
| Material: | Copper Alloy 642 Overall Or Copper Alloy 630 Overall |
| Material Document And Classification: | Qq-c-465 Fed Spec Single Material Response Overall Or Mil-b-6946 Mil Spec Single Material Response Overall Or Ams 4640 Assn Std Single Material Response Overall |
| Style Designator: | 22c Solid, External Flange One End |
| Specification/standard Data: | 80205-nas77 Professional/Industrial Association Standard |

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77A5-028> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.