

## P/N NAS77A5-028

### **Description**

NAS77A5-028 Sleeve Bushing

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS77A5028 Minimum Qty (MOQ): NSN:

3120-01-478-5701

ECCN: EAR99

National Motor Freight: 114800, Bearing, roller, thrust



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS77A5-028 Specifications

Overall Length:	0.3320 Inches Minimum And 0.3470 Inches Maximum
Body Outside Diameter:	0.4381 Inches Minimum And 0.4386 Inches Maximum
Body Inside Diameter:	0.3125 Inches Minimum And 0.3140 Inches Maximum
Flange Outside Diameter:	0.5520 Inches Minimum And 0.5720 Inches Maximum
Flange Width:	0.0570 Inches Minimum And 0.0620 Inches Maximum
Corner Shape:	Square All Corners
Part Name Assigned By Controlling Agency:	Bushing, Flanged
Material:	Copper Alloy 642 Overall Or Copper Alloy 630 Overall
Material Document And Classification:	Qq-c-465 Fed Spec Single Material Response Overall Or Mil-b-6946 Mil Spec Single Material Response Overall Or Ams 4640 Assn Std Single Material Response Overall
Style Designator:	22c Solid, External Flange One End
Specification/standard Data:	80205-nas77 Professional/industrial Association Standard

## **How to Order**

Order this sleeve bushing from our inventory online by visiting <a href="https://military-fasteners.com/bushings/NAS77A5-028">https://military-fasteners.com/bushings/NAS77A5-028</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/NAS77A5-028">https://military-fasteners.com/bushings/NAS77A5-028</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bushings/NAS77A5-028">https://military-fasteners.com/bushings/NAS77A5-028</a> and selecting the quantity you