

P/N NAS77A6-025P

Description

NAS77A6-025P Sleeve Bushing

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS77A6025P

Minimum Qty (MOQ):

NSN: 3120-00-554-4304

ECCN: EAR99

National Motor Freight: 114870, Bearing / Bushing Metal



^{*} See page 2 for technical characteristics

P/N NAS77A6-025P Specifications

Over well I a worth v	0.2020 la ab ao Minimura And 0.2170 la ab ao Mariana
Overall Length:	0.3020 Inches Minimum And 0.3170 Inches Maximum
Body Outside Diameter:	0.5006 Inches Minimum And 0.5013 Inches Maximum
Body Inside Diameter:	0.3750 Inches Minimum And 0.3765 Inches Maximum
Flange Outside Diameter:	0.6150 Inches Minimum And 0.6350 Inches Maximum
Flange Width:	0.0570 Inches Minimum And 0.0620 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Left Flange Outside Right Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Corner Shape:	Undercut Left Flange Body Corner
Surface Finish:	100.0 Microinches Intermediate Layer
Material:	Copper Alloy 642 Overall
Material Document And Classification:	Qq-c-465 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	22c Solid, External Flange One End
Style Designator:	Solid, External Flange One End
Specification/standard Data:	80205-nas77 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting https://military-fasteners.com/bushings/sleeve+bushings/NAS77A6-025P and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.