

Description

Length: 1/4",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------------------|
| SKU / Model: | NAS77A8025 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 3120-01-282-2217 |
| ECCN: | EAR99 |
| National Motor Freight: | 114870, Bearing / Bushing Metal |



* See page 2 for technical characteristics

P/N NAS77A8-025 Specifications

| | |
|----------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Overall Length: | 0.3120 Inches Nominal |
| Body Outside Diameter: | 0.6257 Inches Minimum And 0.6265 Inches Maximum |
| Body Inside Diameter: | 0.5000 Inches Minimum And 0.5015 Inches Maximum |
| Flange Outside Diameter: | 0.7400 Inches Minimum And 0.7600 Inches Maximum |
| Flange Width: | 0.0570 Inches Minimum And 0.0620 Inches Maximum |
| Corner Shape: | Chamfered Inside Right Corner |
| Corner Shape: | Chamfered Inside Left Corner |
| Corner Shape: | Square Left Flange Outside Right Corner |
| Corner Shape: | Square Outside Left Corner |
| Corner Shape: | Square Outside Right Corner |
| Corner Shape: | Undercut Left Flange Body Corner |
| Surface Finish: | 100.0 Microinches Overall |
| Material: | Copper Alloy 642 Overall Or Copper Alloy 630 Overall |
| Material Document And Classification: | Qq-c-00465 Fed Spec All Material Responses Overall Or Ams 4640 Assn Std 2nd Material Response Overall |
| Style Designator: | 22c Solid, External Flange One End |
| Specification/standard Data: | 80205-nas77 Professional/industrial Association Standard |

How to Order

Order this sleeve bushing from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS77A8-025> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.