

P/N NAS77A8-025

Description

Length: 1/4",

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS77A8025

Minimum Qty (MOQ): 5

NSN: 3120-01-282-2217

ECCN: EAR99

National Motor Freight: 114870, Bearing / Bushing Metal









^{*} See page 2 for technical characteristics

P/N NAS77A8-025 Specifications

Overall Length:	0.3120 Inches Nominal
Body Outside Diameter:	0.6257 Inches Minimum And 0.6265 Inches Maximum
Body Inside Diameter:	0.5000 Inches Minimum And 0.5015 Inches Maximum
Flange Outside Diameter:	0.7400 Inches Minimum And 0.7600 Inches Maximum
Flange Width:	0.0570 Inches Minimum And 0.0620 Inches Maximum
Corner Shape:	Chamfered Inside Right Corner
Corner Shape:	Chamfered Inside Left Corner
Corner Shape:	Square Left Flange Outside Right Corner
Corner Shape:	Square Outside Left Corner
Corner Shape:	Square Outside Right Corner
Corner Shape:	Undercut Left Flange Body Corner
Surface Finish:	100.0 Microinches Overall
Material:	Copper Alloy 642 Overall Or Copper Alloy 630 Overall
Material Document And Classification:	Qq-c-00465 Fed Spec All Material Responses Overall Or Ams 4640 Assn Std 2nd Material Response Overall
Style Designator:	22c Solid, External Flange One End
Specification/standard Data:	80205-nas77 Professional/industrial Association Standard

How to Order

Order this sleeve bushing from our inventory online by visiting https://military-fasteners.com/bushings/sleeve+bushings/NAS77A8-025 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bushings/sleeve+bushings/NAS77A8-025 and selecting the quantity