

Description

Fastener Length: 1/2", Thread: 8-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7802U3
Minimum Qty (MOQ):	25 EA
NSN:	5305-01-612-7997
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS7802U3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.511 Inches Nominal
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Grip Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Internal Drive Style:	Cross Recess Type li
Nominal Thread Diameter:	0.1640 Inches
Grip Length:	0.188 Inches Nominal
Thread Quantity Per Inch:	32
Material:	Iron Alloy 660 Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7802U3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.