

Description

Fastener Length: 3/4", Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS7802U5
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-612-8000
Schedule B:	7318.15.8085
ECCN:	EAR99



NO IMAGE
AVAILABLE

P/N NAS7802U5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.730 Inches Minimum And 0.760 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Grip Diameter:	0.163 Inches Nominal
Internal Drive Style:	Cruciform Ribbed
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Nonstandard Thread Pitch Diameter:	+0.132 To 0.164 Inches
Thread Quantity Per Inch:	32
Part Name Assigned By Controlling Agency:	Bolt,pan Head,close Tolerance,short Thread,cruciform Recess,a286 Cres,nonlocking
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams 5732 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response Or Ams 5853 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	-qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bushings/sleeve+bushings/NAS7802U5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.