

Description

Fastener Length: 61/64", Thread: 10-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7803LU10
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-412-7487
National Motor Freight:	096640, Screws, Iron Or Steel



\* See page 2 for technical characteristics

## P/N NAS7803LU10 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.933 Inches Minimum And 0.963 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.357 Inches Minimum And 0.373 Inches Maximum
<b>Head Height:</b>	0.122 Inches Minimum And 0.133 Inches Maximum
<b>Locking Feature:</b>	Patch Threads Or Pellet Threads Or Strip Threads
<b>Grip Diameter:</b>	0.1890 Inches Minimum And 0.1895 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas7803 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS7803LU10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.