

Description

Fastener Length: 25/64", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7803U1
Minimum Qty (MOQ):	25 EA
NSN:	5305-01-585-5779
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS7803U1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.370 Inches Minimum And 0.400 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Grip Diameter:	0.189 Inches Minimum And 0.190 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.052 Inches Minimum And 0.072 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt Pan Head Close Tolerance Short Thread Cruciform Recess A286 Cres Self Locking And Non Locking
Special Features:	Item Has Unplated Bolts
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS7803U1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.