

Description

NAS7903A6 Close Tolerance Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS7903A6
Minimum Qty (MOQ):	2
NSN:	5305-01-471-9389
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS7903A6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.675 Inches Minimum And 0.713 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
End Item Identification:	Support Or Pre-provisioning Items For Which Navicp-phil Acts As Poe
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:	32
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Bolt,pan Head,close Tolerance,short Thread,cruciform Recess,titanium Alloy Gal-4v,self-locking And Nonlocking
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams 4928 Assn Std 1st Material Response Overall Or Ams 4967 Assn Std 2nd Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Nas 4006 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS7903A6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.