

P/N NAS8000-24

Description

Fastener Length: 1-39/64", Thread: 4-40, Thread Length: 1-39/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS800024
Minimum Qty (MOQ): 1 EA

NSN: 5305-00-078-0184

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS8000-24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.510 Inches Minimum And 1.620 Inches Maximum
Fastener Length:	1.560 Inches Minimum And 1.620 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740
Screw Material Document And	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material
Classification:	Response
Screw Surface Treatment:	Cadmium And Chromate
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas600 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS8000-24 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.