

P/N NAS8100U5

Description

NAS8100U5 Machine Screw

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS8100U5
Minimum Qty (MOQ):	50
NSN:	5305-01-228-4229
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS8100U5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.232 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.282 Inches Minimum And 0.312 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas8100 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS8100U5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.